



# CHEMICAL REACTIVITY OF CANEY SHALE TO KCL-BRINES AT ELEVATED TEMPERATURE AND PRESSURE

**Presenter: Gabriel Adua Awejori**

**Awejori, G.A., Fengyang, X., Luo, G., Grider, C., Katende, A., Radonjic, M.**

Oklahoma State University, Stillwater, Oklahoma, USA

**Doughty, C., Spycher, N.**

Energy Geosciences Division, Lawrence Berkeley National Laboratory, Berkeley, California, USA

**Paronish, T.**

Leidos Research Support Team, National Energy Technology Laboratory, Morgantown, West Virginia, USA

**O'Connell, L.**

Stim-Lab Inc., Duncan, Oklahoma, USA

**Rihn, A.**


Continental Resources, Oklahoma City, Oklahoma, USA

**DOE Award DE-FE0031776 from the Office of Fossil Energy in Partnership with** Continental Resources, OGS, OSU Geology, OSU Chem. Engineering, University of Pittsburgh, Lawrence Berkeley National Lab and DOE NETL.

**AIChE Annual Meeting 2021, BOSTON, MASSACHUSETTS**

# PRESENTATION OUTLINE

- ❑ Introduction
- ❑ Objectives
- ❑ Materials and Methodology
- ❑ Results
- ❑ Conclusions and Recommendations




*Retrieved Core from Caney Shale on Display*

# SUMMARY

- Geochemical reactions between rocks and engineered fluids impact petrophysical properties of a formation
- The impacts of these reactions are particularly prominent in micro-fractures and nano-fractures (scale) as opposed to geomechanical forces which act more on macro-fractures more
- Micro-fractures and nano-fractures form extensive networks that reach deep into the reservoir thus very important
- They serve as conduits for hydrocarbon transport to the main fractures and then to the well
- Therefore, any adverse rock-fluid interactions in these zones can greatly reduce permeability thus, productivity from a reservoir
- This research focuses on rock-fluid interactions and their adverse outcomes as well as geomechanical stress impacts on fracture face
- Our work focuses on Caney Shale play South Central Oklahoma Oil Province

# INTRODUCTION

- The Caney shale is a newly discovered unconventional reservoir in South Central Oklahoma
- Though known to contain substantial amounts of hydrocarbon, it was designated a seal and/or source rock due to its high clay content
- Advancements in hydraulic fracturing technologies has however unveiled the potential of the Caney Shale
- Recent drilling and exploitation has revealed adverse rock-fluid interactions in the formation
- Geochemical characterization is essential to understanding these interactions and to improving recovery efficiency






# OBJECTIVES

Investigate rock responses to HFFs. Key concerns are:


- Migration of fines (Caney shale has high illite composition)
- Swelling clays and detachment of clay layers
- Dissolution and precipitation of minerals
- Impact of these in occluding fractures and cutting of the connection between well and reservoir

## Fracture and near-fracture clay-fluid reactions after hydraulic fracturing



# MATERIALS AND METHODOLOGY

## Three-Pronged Approach: Experiment, Simulation and Logging



# MATERIALS AND METHODOLOGY

## Batch Experiment

- Designed to mimic shut-in period
- Undertaken at Temperature of 90°C and atmospheric pressure
- Initial Liquid to powdered sample ratio of 20:1 (140mL:0.7g)
- Sampling done on days: 1, 4, 7, 14, 21 and 28 (10mL sample)

## Conductivity Test

- Proppant (40/70) sandwiched between half piece of core sample
- Changing Stresses applied, 4000-12000 and back to 4000
- Width, Permeability and Conductivity measured

## Materials Used:

Three fluid samples of varying compositions:

- 2% Potassium Chloride Solution (pH~4)
- 0.5% Choline Chloride Solution (pH~4)
- Deionized Water (Base, pH~7)

Three rock samples selected at different depths:

- High Quartz (HQ)  
[74.4% Quartz, 9.6% Carbonate and 16% Clay]
- Moderate Quartz, Carbonate and Clay (MQ)  
[63.1% Quartz, 17.1% Carbonate and 19.8% Clay]
- High Clay (HC)  
[41.5% Quartz, 14.1% Carbonate and 44.4% Clay]


# RESULTS

Identifying the key driving force that can cause varying outcomes for rock-fluid interactions


Question: Is it the fluid or it is the rock?

Answer: Obviously the fluid

Impact of Fluid Composition on elemental concentration in effluent



Impact of Rock Composition on Elemental Concentration in effluent






# RESULTS

## Calcium ion:




- Ca ion concentration distinguishable for each fluid type
- Ca ions in solution believed to be from Calcite and Dolomite Dissolution
- Potassium Chloride>Choline Chloride>Deionized water (In terms of ion concentration in solution)
- HQ and MQ samples have higher concentrations than HC sample



# RESULTS

## Sulphate ion:

- $\text{SO}_4$  ion concentration distinguishable for each fluid type
- $\text{SO}_4$  ions in solution believed to be mainly contributed from the Dissolution of Pyrite
- Potassium Chloride > Choline Chloride > Deionized water (In terms of ion concentration in solution)
- HQ and MQ samples have higher concentrations than HC sample



● HQDI ■ HQKCI ▲ HQCCI




● MQDI ■ MQKCI ▲ MQCCI

● HCDI ■ HCKCI ▲ HCCCI

# RESULTS

## Silicon ion:


- Si ion concentration for various fluids clearly distinguishable
- Si ions in solution believed to be from quartz and clay minerals
- Potassium Chloride>Choline Chloride>Deionized Water (In terms of ion concentration in solution)
- Si ions most likely from the clay and feldspathic component of the rock



# RESULTS



Al and Mg ions show sharp decline in concentrations: Two theories exists:

- Precipitation
  - Substitution or Adsorption
- Aluminum elements in solution are from dissolution and cation exchange in clay minerals
  - Magnesium elemental concentration is mainly from dissolution of dolomite, but clay dissolution and cation exchange in clays may also contribute



# RESULTS

## Stress Impact on Width, Permeability and Conductivity









# RESULTS

## Stress Effect on Conductivity


40/70 + Ductile 2-2, 3B & 6A								
Stress (psi)	2000	4000	6000	8000	10000	12000	6000	4000
Conductivity (md-ft)	1376	952	428	150	62	25	31	32
40/70 + Reservoir 3-1, 2B & 7A								
Stress (psi)	2000	4000	6000	8000	10000	12000	6000	4000
Conductivity (md-ft)	1263	878	481	208	76	37	40	41
40/70 + Reservoir 3-2, 2B & 7A								
Stress (psi)	2000	4000	6000	8000	10000	12000	6000	4000
Conductivity (md-ft)	1466	948	435	173	70	32	36	39
40/70 + Ductile 2-1, 2B & 7A								
Stress (psi)	2000	4000	6000	8000	10000	12000	6000	4000
Conductivity (md-ft)	1451	744	301	118	43	20	22	23

# RESULTS

Except pH values, modelled values and experimental values showed significant disparities



# RESULTS



Three informal Divisions based on XRF results:

- **Upper Caney** shows decreased Si concentration through heavily bioturbated intervals and Al and Fe rich intervals (Clay and Carbonate Rich Zone)
- For the **middle Caney**, Al and Si concentrations remain consistent whilst Ca is low (Quartz-rich shale zone)
- In the **lower Caney**, sharp increase in Ca is observed whilst Al and Si constant (Carbonate zone followed by High Quartz Shale)

# CONCLUSIONS AND RECOMMENDATIONS

## Conclusions:

- Rock-fluid interaction during hydraulic fracturing is largely the function of fluid composition
- Carbonates and Clays are more susceptible to geochemical interactions whilst Quartz is relatively stable
- Increasing clay composition in samples impact dissolution of quartz and carbonate minerals thus less fracture opening
- Potassium Chloride and Choline Chloride stabilized clay minerals
- Mechanism of stabilization is continuous exchange of ions between clays and fluid
- This will help prevent swelling and disintegration of clays thus micro and nano-fractures remain open
- Sustainability of stabilization looks unlikely??

- Substitution of ions may be responsible for low Al and Mg ion concentration since these ions are both exchangeable cations
- Stress has an impact on permeability and conductivity, though limited
- Conductivity of ductile samples is higher per unit change in fracture width

## Recommendations:

- Working on improving geochemical and physical characterization for modelling in our next work
- Further work to be done to clearly understand Al and Mg ion concentration trends
- Longer experiments to determine the limits of effectiveness of temporary clay stabilizers considering pH values continued increasing for entire batch experiment

# ACKNOWLEDGEMENTS

The authors acknowledge:

- DOE Award DE-FE0031776 from the Office of Fossil Energy's, Oil and Natural Gas Program, U.S. Department of Energy
- Joseph Renk, Technical Project Officer, National Energy Technology Laboratory
- Lisa Whitworth and Brent Johnson of Oklahoma State University Microscopy Laboratory
- Adam Haecker and Barry Dean of Continental Resources for providing Caney well production histories.
- The authors would also like to thank George King for guidance
- Vissa Vamsikrishna and Cody Massion of Oklahoma State University



# REFERENCES

1. Dove, P.M. 1995. Kinetic and thermodynamic controls on silica reactivity in weathering environments, in: White, A.F. and Brantley, S.L. (eds). *Chemical Weathering Rates of Silicate Minerals*. pp. 235–290.
2. Knauss, K.G., and T.J. Wolery. 1988. The dissolution kinetics of quartz as a function of pH and time at 70 C. *Geochim. Cosmochim. Acta* 52, 43–53.
3. Olabode, A.O. 2017. Diagenesis and Formation Stress in Fracture Conductivity of Shaly Rocks; Experimental-Modelling Approach in CO<sub>2</sub>-Rock Interactions.
4. Tester, J.W., W.G. Worley, B.A. Robinson, C.O. Grigsby, and J.L. Feerer. 1994. Correlating quartz dissolution kinetics in pure water from 25 to 625C. *Geochim. Cosmochim. Acta* 58, 2407–2420.